

Download our full installation and warranty guides at: www.themasterscraft.com/installation

RECOMMENDED FLOORING ADHESIVES

Follow adhesive & flooring manufacturer's instructions. Replace trowel according to instructions or every 200 sqft.



REAL WOOD ADHESIVE Moisture-cured Urethane
ENGINEERED FLOORS: Up to 6" wide
SOLID FLOORS: No
APPROX. PRICE/SQFT: \$0.29 (Estimate only)
CONTAINER SIZE: 5 gal
SUBFLOOR REQUIREMENTS: 3 lbs/1000 sqft (ASTM 1869) or less than 4.5 on Trammel Concrete Moisture Encounter Meter.

RECOMMENDED TROWEL
ENGINEERED: 3/16" x 14" x 1/2" V-Notch
COVERAGE: 55 sqft/gal



REAL WOOD COHESIVE 2-in-1 Moisture-cured Urethane & Sealer
ENGINEERED FLOORS: Up to 7" wide & 5/8" thick
SOLID FLOORS: Up to 5" wide
APPROX. PRICE/SQFT: \$0.56 (Estimate only)
CONTAINER SIZE: 5 gal
SUBFLOOR REQUIREMENTS: Up to 10 lbs/1000sqft (ASTM 1869) or less than 4.5 on Trammel Concrete Moisture Encounter Meter. Not approved for solid floors below grade.

RECOMMENDED TROWEL
ENGINEERED: 1/4" x 1/4" V-Notch
SOLID: 1/4" x 1/4" V-Notch
COVERAGE: 30-40 sqft/gal



WAKOL MS-230 MS Polymer
ENGINEERED FLOORS: Any width
SOLID FLOORS: Up to 4" wide
APPROX. PRICE/SQFT: \$0.43 (Estimate only)
CONTAINER SIZE: 3 gal
SUBFLOOR REQUIREMENTS: Up to 12 lbs. /1000 sq. ft. / 24 hour (ASTM F 1869) or up to 90 % rH (ASTM F 2170-02).

RECOMMENDED TROWEL
ENGINEERED: 1/4" x 1/4" x 9/16" V-Notch
SOLID: 1/4" x 1/4" x 7/16" V-Notch
COVERAGE: 50-70 sqft/gal



WAKOL MS-260 MS Polymer
ENGINEERED FLOORS: Any width
SOLID FLOORS: Up to 8" wide
APPROX. PRICE/SQFT: \$0.49 (Estimate only)
CONTAINER SIZE: 3 gal
SUBFLOOR REQUIREMENTS: Up to 12 lbs. /1000 sq. ft. / 24 hour (ASTM F 1869) or up to 90 % rH (ASTM F 2170-02).

RECOMMENDED TROWEL
ENGINEERED: 1/4" x 1/4" x 9/16" V-Notch
SOLID: 1/4" x 1/4" x 7/16" V-Notch
COVERAGE: 50-70 sqft/gal



WAKOL MS-290 MS Polymer
ENGINEERED FLOORS: No limitations
SOLID FLOORS: No limitations
APPROX. PRICE/SQFT: \$0.80 (Estimate only)
CONTAINER SIZE: 3 gal
SUBFLOOR REQUIREMENTS: Up to 12 lbs. /1000 sq. ft. / 24 hour (ASTM F 1869) or up to 90 % rH (ASTM F 2170-02).

RECOMMENDED TROWEL
ENGINEERED: 1/4" x 1/4" x 9/16" V-Notch
SOLID: 1/4" x 1/4" x 7/16" V-Notch
COVERAGE: 50-70 sqft/gal



WAKOL PU-280 Roll-on moisture barrier *FASTEST, FULLY-WARRANTED MOISTURE BLOCKER ON THE MARKET!*
ENGINEERED/SOLID FLOORS: No limitations
APPROX. PRICE/SQFT 1 COAT: \$0.19 (Estimate only)
APPROX. PRICE/SQFT 2 COAT: \$0.38 (Estimate only)
CONTAINER SIZE: 2.5 gal
SUBFLOOR REQUIREMENTS: **One coat:** up to 12 lbs. /1000 sq. ft. / 24 hour (ASTM F 1869) or up to 90 % rH (ASTM F 2170-02). **Two coats:** up to 18 lbs. / 1000 sq. ft. / 24 hours (ASTM F 1869) or up to 98 % rH (ASTM F 2170-02)

1 COAT COVERAGE: 500 sqft/gal
2 COAT COVERAGE: 250 sqft/gal



GAL FLOOR EUROBOND D3 Floating floor glue
ENGINEERED FLOORS: 4" or wider
SOLID FLOORS: No
CONTAINER SIZE: 16 oz. bottle
COVERAGE: 124-200 sqft / bottle
SUBFLOOR REQUIREMENTS: Clean, dry, sound & flat.

RECOMMENDED FASTENERS & NAILING SCHEDULES

FLOOR TYPE	FASTENER	LENGTH	GAGE	NAILING SCHEDULE
Solid Floors 3/4"	Staples/Cleats	1-1/2 - 2"	16	Every 6-8" and 1-2" from ends.
Engineered Floors 1/2" or less	Staples/Cleats	1-1/2"	18	Every 4-6" and 1-2" from ends.
Engineered Floors 9/16" or 5/8"	Staples/Cleats	1-3/4"	18	Every 4-6" and 1-2" from ends.
Engineered Floors 3/4"	Staples/Cleats	1-1/2" -2"	16	Every 6-8" and 1-2" from ends.